

Qbini surface box 2x LED Tre dim GI

131202XX

1

11mm
0.2 - 4mm²
24 - 12 AWG

164 mm
135,5 mm
82 mm
12 mm
80 mm
CONNECTION AREA PRIMARY WIRES!

WALL MOUNTING
ONLY HORIZONTAL

2

SCREWS ARE NOT INCLUDED

check dimmer & driver compatibility

3

DO NOT COMBINE THIS SURFACE BOX WITH WARM DIM LED-MODULES!
FOR WARM DIM USE SURFACE BOX 131205XX.

LED-MODULE NEEDS TO BE ORDERED SEPERATELY.

CONNECT LED MODULES IN SERIES

220-230V
50-60Hz
LED DRIVER

4.1 FIRST LATCHED POSITION

4.2 PUSH module UP for SECOND LATCHED POSITION

4.3 PUSH module further UP for RELEASE POSITION

4.4 PULL module DOWN to remove

PREVENTING ELECTROSTATIC DAMAGE

A discharge of static electricity may damage sensitive components. Always be properly grounded when touching leads or circuitry inside the luminaire. Use a wrist strap connected by a ground cord to the housing. Avoid touching the light sources with bare hands.

DRIVERS & ACCESSORIES

For latest version of driver matrix and available accessories check www.supermodular.com or connect with your sales contact.