

FLOS



05.1037.14ANI Black/Bronze

Light Shadow Fixed Trim Mains dimming Version 2 Spots Optic Wide Flood NEW


Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|-------------------|---------------------|
| Mounting | Ceiling recessed |
| Environments | Indoor dry location |
| Light Source Type | LED |
| LED type | Power LED |
| Number of heads | 1 |
| Power (W) | 6.5 |
| System power (W) | 7 |
| Source flux (lm) | 570 |
| System flux (lm) | 391 |

Physical

| | |
|---------------------|--------------|
| Colour | Black/Bronze |
| Trim | Yes |
| Orientation | Fixed |
| Recessed depth (mm) | 75 |
| Length (mm) | 77 |
| Net weight (kg) | 0.25 |
| IP internal | 20 |
| IP external | 55 |

Download

[Mounting instructions](#) PDF

Photometric Files

[LDT / IES](#) ZIP

Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



Schematic light drawing




Beam Angle: 41°


| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 917 | 0.74 |
| 2 | 229 | 1.48 |
| 3 | 102 | 2.22 |
| 4 | 57 | 2.96 |
| 5 | 37 | 3.70 |

Luminous flux luminaire
391 lm (EXTREME CUT OFF)

Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional

Photometric

| | |
|--------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 3000 |
| CRI> | 90 |
| LED Life / Failure Ratio | L80B50 |
| Beam angle C0-180 (°) | 46 |
| Beam angle C90-270 (°) | 46 |

Electrical

| | |
|----------------------|-------------------|
| Insulation class | II |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| LED voltage Vf (Vdc) | 7.2 |
| LED current (mA) | 900 |
| Driver | Remote included |
| Dimmable | Yes |
| Dimming type | Mains Cut Dimming |

Notes

Pre-installation frame not required.